

# Real solutions. Real metal to plastic choices.

Industry regulations and consumer demands change frequently — and as a result, so do your product needs. Let us help you understand how to reduce your product's weight and cost all while maintaining performance and quality.

## Benefits of choosing plastic over metal:

- ▶ Cost reduction
- ▶ Weight reduction
- ▶ Design freedom
- ▶ Secondary operation elimination
- ▶ Parts consolidation
- ▶ Inherent corrosion resistance
- ▶ Longer tool life

## Typical metal die-cast competition:

- ▶ Aluminum
- ▶ Magnesium
- ▶ Zinc

Type of Material	Abbreviation(s)	Recommended Tool Temperature (°C)	Hot Water Moldable	Surface Appearance	Heat Deflection at 264 psi (°C)	Tensile Strength (MPa)	Flexural Modulus (MPa)	Wear and Friction	Chemical Resistance	Tradenames	Advantages
High Performance Polyamide	HPPA	80-140	Yes	Better	255	285	21,500	Better	Better	SYENSQO Omnix®	<ul style="list-style-type: none"> <li>• Excellent colorability</li> <li>• Higher heat resistance and lower moisture uptake than PA 6/6</li> </ul>
Polyarylamide	PARA, PA MXD6	120-160	—	Best	255	290	33,000	Better	Better	Mitsubishi Reny® SYENSQO Ixef®	<ul style="list-style-type: none"> <li>• Low moisture uptake for great dimensional stability</li> <li>• Great retention of mechanicals even at elevated temperatures</li> </ul>
Polyetheretherketone	PEEK	175-205	—	Better	332	258	30,000	Best	Best	SYENSQO KetaSpire®	<ul style="list-style-type: none"> <li>• Inherently V-0 flame rated</li> <li>• Excellent chemical resistance</li> </ul>
Polyetherimide	PEI	135-165	—	Better	212	179	11,700	Good	Better	SABIC's Specialties business ULTEM™	<ul style="list-style-type: none"> <li>• Inherently V-0 flame rated</li> <li>• Good clarity</li> <li>• Plateable</li> <li>• Fire-Smoke-Toxicity (FST) compliant</li> </ul>
Polyphenylene Ether + Polystyrene	PPE+PS	180-250	Yes	Better	148	165	11,700	Good	Better	SABIC's Specialties business NORYL™	<ul style="list-style-type: none"> <li>• Low moisture uptake for great dimensional stability</li> <li>• Great property retention after outdoor UV exposure</li> <li>• Excellent resistance to chlorine treated water for potable water applications</li> </ul>
Polyphthalamide	PPA	65-180	Yes	Better	310	280	22,800	Better	Better	SYENSQO Amodel® ENVALIOR FORTII® & FORTII® ACE	<ul style="list-style-type: none"> <li>• Lower and slower moisture uptake than PA 6/6</li> <li>• Great retention of mechanicals even at elevated temperatures and high humidity</li> </ul>
Polyethersulfone	PESU	120-160	—	Better	216	126	8,070	Good	Better	SYENSQO Veradel®	<ul style="list-style-type: none"> <li>• Improved isotropic shrinkage and CLTE leading to better dimensional stability</li> <li>• High RTI</li> <li>• Good chemical resistance</li> <li>• Inherently V-0 flame rated</li> </ul>

\*HDT, Tensile, and Flex all based on grade with the highest value

## Long fiber compounds: LNP™ VERTON™ from SABIC's Specialties business

### Advantages

- Hot water moldable grades available
- High stiffness and heat deflection
- Availability in many different base resins


## Specific Gravity Comparison

Material	Specific Gravity (g/cm <sup>3</sup> )
Zinc	6.5
Magnesium	1.74
Aluminum	2.7
50% Glass PPA	1.67
50% Glass PARA	1.65
50% Glass HPPA	1.59
40% Glass PPE+PS	1.40
40% Glass PEI	1.61
30% Glass PESU	1.58
30% Glass PEEK	1.53

## Weight vs. Strength Comparison

Plastics show greater specific strength\* compared to metals, allowing applications to meet the strength requirements while reducing weight

### Material



6467 Waldon Center Drive, Clarkston, MI 48346  
248-620-2120 • orders 800-232-4273  
fax 248-620-3192

ChasePlastics.com



Specific Tensile Strength (MPa/Kg)

Tensile Strength (MPa)

\*Specific strength is a material's strength (force per unit area at failure) divided by its density. It is also known as the strength-to-weight ratio or strength/weight ratio.

The marks identified herein are registered trademarks of their respective owners. Any recommendation by Chase Plastics' personnel for the use of any material is based on tests or experience believed to be reliable. However, since the final processing and use of the product are beyond our control, we make no warranty as to such use or effects incidental to such use, handling or sale.  
© February 2024, Chase Plastic Services, Inc.