

## Real solutions. Real electronics choice.

In the performance-driven market of electrical and electronic components, our industry-leading product line meets the most stringent material requirements, offering the most competitive mechanical, thermal, electrical and flame-retardant properties.

Material	Flame Rating	RTI Electric	RTI Impact	RTI Strength	Chemical Resistance	Flowability (For Thin Walls)
<b>Ascend Performance Materials</b>						
Vydyne® Nylon 6/6 & 66/6	5VA at 1.5mm	130°C	95°C	110°C	Good	Excellent
<b>LANXESS Corporation</b>						
Durethan® Nylon 6	5VA at 1.0mm	140°C	120°C	155°C	Good	Excellent
Pocan® PBT	5VA at 1.5mm	130°C	130°C	140°C	Good	Excellent
Pocan® PC/PBT	5VA at 1.5mm	140°C	75°C	130°C	Good	Good
<b>LG Chem America, Inc.</b>						
Keyflex® COPE	V-0 at 1.5mm	50°C	50°C	50°C	Excellent	Good
LG ABS	5VA at 2.0mm	85°C	85°C	85°C	Fair	Good
Lupox® PBT	5VA at 2.5mm	130°C	120°C	120°C	Good	Excellent
Lupox® PC/PBT	5VA at 2.3mm	130°C	120°C	120°C	Good	Good
Lupoy® PC	5VA at 2.5mm	120°C	115°C	120°C	Fair	Good
Lupoy® PC/ABS	5VA at 1.5mm	60°C	60°C	60°C	Fair	Good
<b>Mitsubishi Engineering Plastics Corporation</b>						
lupilon® PC	5VA at 2.5mm	120°C	120°C	125°C	Fair	Good
<b>SABIC's Specialties business</b>						
LEXAN™ Copolymer resins (PC Copolymer)	5VA at 3.0mm	125°C	120°C	125°C	Fair	Good
NORYL™ resin (PPE+PS)	5VA at 2.0mm	140°C	85°C	125°C	Good	Excellent
ULTEM™ resin (PEI)	5VA at 1.5mm	170°C	170°C	170°C	Good	Good
<b>Solvay Specialty Polymers</b>						
Amodel® PPA	5VA at 1.5mm	130°C	130°C	130°C	Excellent	Excellent
Radel® PPSU	5VA at 1.5mm	160°C	160°C	160°C	Excellent	Excellent
Ryton® PPS	5VA at 1.5mm	240°C	220°C	240°C	Excellent	Excellent
Udel® PSU	V-0 at 4.4mm	160°C	140°C	160°C	Excellent	Good
Veradel® PESU	5VA at 1.5mm	180°C	170°C	180°C	Excellent	Good
<b>Teknor Apex</b>						
Elaxar® TPE	V-0 at 1.2mm	50°C	50°C	50°C	Fair	Good

\*RTI values based on grade(s) with the highest flame rating

### Specialty and engineering thermoplastics for electrical/electronic needs now and in the future

- ▶ Electrically conductive compounds for EMI and RFI shielding
- ▶ High-temperature thermoplastics compatible with surface-mount technology (SMT) and lead-free soldering processes for use in connectors and other components
- ▶ Thermally conductive compounds for thermal management, heating and cooling
- ▶ High-flow resins to meet miniaturization and thin-wall requirements
- ▶ RoHS- and WEEE-compliant compounds to meet “green” initiatives
- ▶ Soft-touch compounds for user comfort


#### Applications include:

- ▶ Connectors
- ▶ Switches
- ▶ Bobbins
- ▶ Capacitors
- ▶ Relays
- ▶ Housings
- ▶ Covers
- ▶ Shields
- ▶ Sockets
- ▶ Circuit Breakers

# Your electronics choice

Specialty and engineering thermoplastics for the electrical/electronics market.

Short-Term Peak Temperature by Material Type



## Copolyester Elastomer (COPE)

- ▶ Excellent fatigue resistance for ease of assembly and continuous vibration
- ▶ Good chemical resistance and halogen-free flame retardancy
- ▶ Grades available in durometers ranging from 28-72 shore D

## Electrically Conductive Compounds

- ▶ Compounds are formulated with additives to achieve the right balance of mechanical properties and resistivity for any point in the EM spectrum
- ▶ Available in a wide range of engineering materials including PA6, PA4/6, PA6/6, PA12, ABS, PC, POM, PPS and more
- ▶ Temperature resistance up to 280°C for soldering (IR and lead-free)
- ▶ Exceptional flow properties with high weld line strength for more robust and reliable connectors than with LCPCs
- ▶ High pin retention strength, capable of withstanding high part assembly forces
- ▶ Outstanding toughness, capable of withstanding high part assembly forces

## Polyamide 6 & 6/6 (PA 6 & PA 6/6)

- ▶ Short-term high temperature resistance (500°F/260°C).
- ▶ Able to withstand lead-free solder temperatures without melting
- ▶ Excellent dielectric strength and comparative tracking index combined with an inherent V2 flame rating, which can be increased to V0 and improved to 5VA in some grades
- ▶ Electrically neutral grades and non-copper based options available
- ▶ High flow grades for thinner walls and longer flow lengths

## Polybutylene Terephthalate (PBT/PET)

- ▶ Excellent dimensional stability
- ▶ High rigidity and strength
- ▶ Outstanding heat aging performance and dielectric strength
- ▶ Improved hydrolytic stability compared to nylons
- ▶ Great electrical insulation properties

## Polycarbonate/Polybutylene Terephthalate (PC/PBT)

- ▶ Excellent toughness even at low temperatures
- ▶ Improved chemical resistance to fuels
- ▶ Excellent weatherability and good UV resistance
- ▶ High color retention

## Copolymer Polycarbonate (PC)

- ▶ Improved chemical resistance, weathering performance and toughness compared to standard polycarbonate
- ▶ Good thin wall flame retardancy while maintaining transparency
- ▶ High heat portfolio combines heat resistance with excellent clarity and color stability
- ▶ Flame, smoke and toxicity compliant grades available

## Polycarbonate (PC)

- ▶ UL94 flame retardant up to 5VA, including non-halogenated options
- ▶ Excellent dimensional stability, clarity and toughness
- ▶ Excellent creep resistance

## Polyetherimide (PEI)

- ▶ Exceptional long term high heat and chemical resistance
- ▶ Among the most dimensionally stable thermoplastics available. Filled grades offer tight dimensional tolerances.
- ▶ Inherent flame resistance without additives in most grades
- ▶ Extremely low smoke generation, flame spread and toxicity
- ▶ Retain strength and resist stress cracking when exposed to automotive and aircraft fluids, aliphatic hydrocarbons, alcohols, acids, and weak aqueous solutions
- ▶ Infrared and microwave transparent

## Polysulfones (PESU, PSU, PPSU)

- ▶ Long term high heat capability
- ▶ Excellent chemical resistance and hydrolytic stability
- ▶ Good electrical (dielectric) properties
- ▶ Sterilizable via multiple methods
- ▶ Clear grades available
- ▶ Resistant to X-ray and microwave radiation

## Polyphenylene Ether (PPE)

- ▶ Excellent dimensional stability, low mold shrinkage and very low creep at elevated temperatures
- ▶ High dielectric strength with excellent electrical properties over a range of temperatures, humidities and frequencies
- ▶ Good chemical resistance to battery acids, bases and many cleaning agents
- ▶ Flexible grades available in 92A-63D durometers

## Polyphenylene Sulfide (PPS)

- ▶ Excellent flow and low shrinkage for precision molding of connectors and sockets
- ▶ Superior stiffness and mechanical integrity for reliable assembly
- ▶ Inherently flame retardant
- ▶ Suitable for all soldering processes (SMT, IR, lead-free)
- ▶ Excellent chemical resistance at elevated temperatures

## Polyphthalamide (PPA)

- ▶ Outstanding electrical properties and high heat resistance allow for electronic components exposed to SMT processing
- ▶ Low moisture uptake resulting in greater dimensional stability
- ▶ Ideal construction material for high temperature, molded interconnecting devices (MIDs) and products requiring lead-free soldering
- ▶ Excellent chemical resistance

## Thermoplastic Elastomer (TPE)

- ▶ Benchmark ductility for flexible connections and cable jacketing down to -60°C
- ▶ UV and ozone resistant grades available
- ▶ Flexible grades available in durometers ranging from 58-90 shore A
- ▶ Phthalate-free grades for REACH and RoHS compliance



6467 Waldon Center Drive • Clarkston, MI 48346  
248-620-2120 • orders 800-232-4273 • fax 248-620-3192

[ChasePlastics.com](http://ChasePlastics.com)

The marks identified herein are registered trademarks of their respective owners. Any recommendation by Chase Plastics' personnel for the use of any material is based on tests or experience believed to be reliable. However, since the final processing and use of the product are beyond our control, we make no warranty as to such use or effects incidental to such use, handling or sale. © May 2020, Chase Plastic Services, Inc.

